

The information contained in this drawing is the sole property of Coil Winding Specialist Inc (CWS). Any reproduction in part or whole without written permission of CWS is prohibited.

## F-114-43C

### Features


NiZn ferrite with a range of 20 to 250 MHz for suppression of conducted EMI, that is used for inductive applications (ex: high frequency common-mode chokes)

Burnished to break sharp edges, can contain Parylene C coat at smaller diameters from length 9.5mm (0.375") or a uniform coating of thermo-set plastic for larger dimension (if part numbers ends with a C).

REVISION HISTORY						
REV	ECN	DESCRIPTION	SIGN & DATE			
			BY	DATE	AP.	DATE
A		Production release	EO	7/23/13	JL	7/23/13

Electrical Specifications				
Item	Unit/Symbol	Condition	Value	Tol.
A <sub>L</sub>	nH/N <sup>2</sup>	@ 10 KHz	510	± 20%
L <sub>c</sub>	cm	N/A	7.3	± 10%
A <sub>e</sub>	cm <sup>2</sup>	N/A	0.37	± 10%
V <sub>e</sub>	cm <sup>3</sup>	N/A	2.7	± 10%
Initial Permeability	μ <sub>0</sub>	@ B < 10 gauss	800	± 20%
Temp. Coeff. Of initial Permeability	%, °C	20 - 70 °C	1.25	Typ.
Coercive Force	H <sub>c</sub>	oersted	0.45	Typ.
Residual Flux Density	Gauss, B <sub>r</sub>	N/A	1300	Typ.
Flux Density	Gauss, B	Initial (B), oersted	2900	Typ.
	Gauss, H	@ Field Strength (H), oersted	10	Typ.
Curie temperature	°C	T <sub>c</sub>	> 130	Nom.
Resistivity	Ω cm, ρ	@ Field Strength	10 <sup>5</sup>	Typ.
Loss Factor	10 <sup>-6</sup> , tanδ / μ	Initial	250	Typ.
	MHz	@ Frequency	1	Typ.

Dimensional Tolerances				
	in	tol.	mm	tol.
Case				
B (Outer Diameter)	1.187	Max	30.15	Max
A (Inner Diameter)	0.708	Min	18.00	Min
H (Height)	0.325	Max	8.25	Max
Weight	13.00 g			



**For additional detail, specifications and charts see:**

[http://www.bytemark.com/products/ferrite\\_matl.htm](http://www.bytemark.com/products/ferrite_matl.htm)

CODE IDENT	MFG. P/N	DESCRIPTION	ITEM NO.
		<b>PARTS LIST</b>	
AUTOCAD	X	www.coilws.com www.cwsbytemark.com	CWSBYTEMARK 353 West Grove Ave. Orange, CA. 92865
SOLIDWORKS			
DRAWN	EO 7/23/13	TITLE: Ferrite Toroid Core Material 43, NiZn, Paralyne Coated	
CHECKED	JL 7/23/13		
ENGR.	JL 7/23/13		
APPR.	JL 7/23/13	SIZE DWG. NO.	REV
		B F-114-43C	A
DO NOT SCALE DRAWING		SCALE	SHEET 1 OF 1
		N/A	